


GP Batteries

Data Sheet

Model No.: GP189


Type	: Alkaline Low Drain Button Cell
Chemical System	: Alkaline Manganese Dioxide
Nominal Voltage	: 1.5Volts
Nominal Dimensions	: Ø11.6mm×3.05mm
Application	: Watch (with alarm), calculator, electronic toys, melody card, ... etc.
Average Weight	: 1.0g
Date Code	: Unless otherwise specified, each cell Will carry a numeric year code and an alphabetical month code.
Shelf Life	: Not less than 90% of the service capacity within first year. , not less than 85% of the service capacity with third year storage at 22 ± 3 °C 40-80%RH.
Close Circuit Voltage	: 1.30 Volts (min.)(load resistor 100Ω at 22 ± 3 °C for 0.1 to 2 seconds)
Nominal Service Life	: 660hrs (at 20 kΩ load) (to 1.0V at 22 ± 3 °C) 140 days (at 100 kΩ load)
Average Service Capacity	: 44mAh(at 15 kΩ load) (to 1.0V at 22 ± 3 °C)

Typical Discharge characteristics at 22 ± 3 °C



Cross References:

IEC	JIS	Eveready	Varta	Duracell
LR54	LR54	189	V10GA	LR54



* The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.

