

GP Batteries

Data Sheet

Model No.: GP476

Description	: Alkaline High Voltage Battery
Nominal Voltage	: 6Volts
Nominal Dimensions	: Ø13.0mm×25.2mm
Terminal	: Nickel plated flat contacts - protruded red(+); recessed black (-)
Jacket	: Metal jacket
Internal Connection	: Pressure
Applications	: Electronic toy, photo
Average Weight	: 11g
Date Code	: Unless otherwise specified, each batteries will carry a numeric year code and analogue month code
Shelf Life	: Not less than 90% of the service capacity within first year. , not less than 85% of the service capacity with third year storage at 22 ± 3 °C 40-80 %RH.
Insulation Resistance	: 5MΩ min.
Close Circuit Voltage	: 5.0 Volts (min.)(load resistor 400Ω at 22 ± 3 °C for 0.1 to 2 seconds)
Nominal Service Life	: 165hrs (at 6kΩ load) (to 5.2V at 22 ± 3 °C)
Average Service Capacity	: 165mAh(at 6kΩ load) (to 5.2V at 22 ± 3 °C)

Cross References:

GP	IEC	JIS	Duracell	Varta
476	4SR44	4SR44	PX28	V28PX

Typical Discharge characteristics at 22 ± 3°C

