



Description	: Silver Oxide Low Drain Button Cell
Nominal Voltage	: 1.55Volts
Nominal Dimensions	: Ø5.80mm×2.15mm
Application	:Analog watch
Average Weight	: 0.25g
Date Code	: Unless otherwise specified, each cell Will carry a numeric year code and an alphabetical month code.
Shelf Life	: Not less than 90% of the service capacity within first year. , not less than 85% of the service capacity with third year storage at 20 ± 2 °C 45-75 %RH.
Close Circuit Voltage	: 1.20 Volts (min.)(load resistor 2KΩ at 20 ± 2 °C for 0.1 to 2 seconds)
Nominal Service Life	: 610hrs (at 68kΩ load) (to 1.2V at 20 ± 2 °C) 185days (at 500kΩ load)
Average Service Capacity	: 14mAh(at 68kΩ load) (to 1.2V at 20 ± 2 °C)



Cross References:

IEC	JIS	Eveready	Varta	Duracell	Panasonic	Sony
SR63	SR63	379	V379	D379	SP379	SR521SW

### Typical Discharge characteristics at 20 ± 2°C



\* The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.