


Description	: Silver Oxide Low Drain Button Cell
Nominal Voltage	: 1.55Volts
Nominal Dimensions	: Ø9.50mm×2.70mm
Application	: Watch (with alarm and lamp), calculator, melody card etc.
Average Weight	: 0.8g
Date Code	: Unless otherwise specified, each cell Will carry a numeric year code and an alphabetical month code.
Shelf Life	: Not less than 90% of the service capacity within first year. , not less than 85% of the service capacity with third year storage at 20 ± 2 °C 45-75 %RH.
Close Circuit Voltage	: 1.30 Volts (min.)(load resistor 200Ω at 20 ± 2 °C for 0.1 to 2 seconds)
Nominal Service Life	: 1050hrs (at 30kΩ load) (to 1.2V at 20 ± 2 °C)      145days (at 100kΩ load)
Average Service Capacity	: 55mAh(at 30kΩ load) (to 1.2V at 20 ± 2 °C)

Model No.: **GP395**




### Cross References:

IEC      JIS      Eveready   Varta   Duracell   Panasonic   Sony

SR57   SR57      395   V395   D395   SP395      SR927SW

### Typical Discharge characteristics at 20 ± 2°C



\* The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.